US006845566B1

(12) **United States Patent**
Clements et al.

(10) **Patent No.: US 6,845,566 B1**
(45) **Date of Patent: Jan. 25, 2005**

(54) **ROTATING FEELER GAGE**

(75) Inventors: **Marvin W. Clements**, Portsmouth, RI (US); **Paul E. Moody**, Barrington, RI (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/672,963**

(22) Filed: **Sep. 29, 2003**

(51) **Int. Cl.**[7] **G01B 3/20**; G01B 3/50

(52) **U.S. Cl.** **33/501.08**; 33/501.45; 33/542

(58) **Field of Search** ..... 33/501.45, 501.08, 33/501.05, 501.06, 542, 544, 544.1, 567, 613, 600, 832–833, 602; 114/201 R

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,656,180 A	*	1/1928	Eisele	33/542
2,901,829 A	*	9/1959	Lucas	33/567
2,903,797 A	*	9/1959	Hackwood	33/501.45
3,319,339 A	*	5/1967	Marconi	33/832
4,004,538 A		1/1977	Schoonman	
4,388,782 A		6/1983	Rodgers et al.	
4,466,551 A		8/1984	Leung	
4,534,135 A		8/1985	Wilger et al.	
4,930,226 A	*	6/1990	Shindelar	33/655
4,945,651 A	*	8/1990	Georg	33/832
5,038,600 A	*	8/1991	Friedman	33/502
5,144,753 A	*	9/1992	Murphy	33/514
5,288,292 A	*	2/1994	Giraud et al.	33/512
5,421,224 A	*	6/1995	Bond	81/436
5,562,065 A		10/1996	Duarte et al.	
5,592,747 A	*	1/1997	Kessler	33/783
6,397,486 B1	*	6/2002	Keys et al.	33/522

* cited by examiner

Primary Examiner—Diego Gutierrez
Assistant Examiner—Yaritza Guadalupe
(74) *Attorney, Agent, or Firm*—James M. Kasischke; Michael P. Stanley; Jean-Paul Nasser

(57) **ABSTRACT**

A feeler gage including a pin member having a first end and an opposing end with a gage connected to the opposing end of the pin member. The gage has a first end connected to the pin and a free end projecting past a peripheral dimension of the pin. An indicator is formed on the first end of the pin member in alignment with a longitudinal axis of the gage for determining a position of the gage upon rotation of the pin member. The gage is of a predetermined thickness and is aligned with the indicator formed at the first end of the pin member. Rotation of the pin member correspondingly rotates the gage of the pin member. If the gage rotates freely, then a gap is determined to be present in the area where the gage is rotated through. If the gage does not rotate freely, then no gap exists.

5 Claims, 5 Drawing Sheets